



Product Specifications

Construction	Textured Loop
Backing	Standard Back
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	24 oz./sy (814 grams/m2)
Pile Density	7200 oz./y3 (266.98 kg/m3)
Pattern Repeat	.20" (w) x .75" (l) approx. (.51cm x 1.91cm)
Gauge	1/8 (3.15 rows/cm)
Stitches Per Inch	8 stitches/in (3.15 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Encore SD Ultima Fiber Standard Back
Optional Warranties	Endure Plus TitanBac Plus

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	25%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways




RHR01 News Radio



RHR02 Mass Tran...




RHR03 Limited Ac...



RHR04 Fast Lane



RHR05 Gridlock



RHR06 Merging Tra...