



## Product Specifications

<b>Wear Layer</b>	20 mil
<b>Thickness</b>	2.5mm
<b>Finish / Coating</b>	UV Cured Urethane
<b>Pattern Repeat</b>	Random Stone
<b>Dimensions:</b>	18" x 36"
<b>Standard Adhesive</b>	Commercialon Premium Modular and LVT Adhesive
<b>Backing Class</b>	Commercial Grade
<b>Commercial Traffic</b>	Heavy Commercial
<b>Standard Warranties</b>	10 Year LVT

## Packaging

<b>Sq.ft. per piece / carton</b>	4.5 / 54
<b>Weight per piece / carton</b>	4.11 (lbs) / 49.36 (lbs)
<b>Pieces per box</b>	12
<b>Boxes per pallet</b>	40

## Special Technologies

<b>Added Antimicrobial</b>	Yes
----------------------------	-----

## Environmental Specifications &amp; Tests

<b>Indoor Air Quality</b>	FloorScore® Certified
<b>LEED v4</b>	Contributes to IAQ: Low Emitting Materials
<b>End of Life</b>	100% Recyclable
<b>Class / ASTM F1700</b>	Class III Printed Film Vinyl Plank - Type B (embossed)
<b>Flooring Radiant Panel</b>	Class 1
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>ASTM F2055 (Size and Tolerance)</b>	Passes
<b>ASTM F386 (Thickness)</b>	Passes
<b>ASTM F1914 (Residual Indentation)</b>	Passes
<b>ASTM F137 (Flexibility)</b>	Passes
<b>ASTM F2199 (Dimensional Stability)</b>	Passes
<b>ASTM F925 (Chemical Resistance)</b>	Passes
<b>ASTM F1514 (Resistance to Heat)</b>	Passes
<b>ASTM F1515 (Resistance to Light)</b>	Passes
<b>ASTM E648 (Critical Radiant Flux)</b>	Passes
<b>ASTM E662 (Optical Smoke Density)</b>	Passes
<b>ASTM C1028 (Slip Resistance)</b>	Passes
<b>ASTM F970 (Static Load)</b>	Passes

## Colorways



00001 Whitewash



00002 Limestone



00003 Dark Ash