



Product Specifications

| | |
|----------------------------|---|
| Construction | Textured Loop |
| Backing | Standard Back |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Ultima® (with recycled content) |
| Face Weight | 25 oz./sy (848 grams/m2) |
| Pile Density | 8654 oz./y3 (320.90 kg/m3) |
| Pattern Repeat | 2.40" (w) x 2.00" (l) approx. (6.10cm x 5.08cm) |
| Gauge | 1/10 (3.94 rows/cm) |
| Stitches Per Inch | 12 stitches/in (4.72 stitches/cm) |
| Standard Width | 12 ft 3.66 m |
| Standard Adhesive | Commercial Premium Carpet Adhesive |
| Standard Warranties | Encore SD Ultima Fiber Standard Back |
| Optional Warranties | Endure Plus TitanBac Plus |

Special Technologies

| | |
|-------------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |

Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Total Recycled Content | 25% |
| Flooring Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |


Colorways



JRN25 Lock & Key




JRN36 Storyline



JRN48 Fine Point



JRN55 Silver Clip



JRN58 Graphite



JRN76 Script