



Product Specifications

Construction	Textured Loop
Backing	Standard Back
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	23 oz./sy (780 grams/m2)
Pile Density	7886 oz./y3 (292.42 kg/m3)
Pattern Repeat	.40" (w) x .50" (l) approx. (1.02cm x 1.27cm)
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	12 stitches/in (4.72 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Encore SD Ultima Fiber Standard Back
Optional Warranties	Endure Plus TitanBac Plus

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	25%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways




MEM25 Diary




MEM36 Entry



MEM48 Rollerball



MEM55 Bookplate



MEM58 Pen & Ink



MEM76 Notebook