



Product Specifications

| | |
|----------------------------|--|
| Construction | Textured Loop |
| Backing | Standard Back |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Ultima® (with recycled content) |
| Face Weight | 26 oz./sy (882 grams/m2) |
| Pile Density | 5318 oz./y3 (197.19 kg/m3) |
| Pattern Repeat | N/A |
| Stitches Per Inch | 12.66 stitches/in (4.98 stitches/cm) |
| Standard Width | 12 ft 3.66 m |
| Standard Adhesive | Commercialon Premium Carpet Adhesive |
| Standard Warranties | Encore SD Ultima Fiber Standard Back |
| Optional Warranties | Endure Plus TitanBac Plus |

Special Technologies

| | |
|-------------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |

Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Total Recycled Content | 25% |
| Flooring Radiant Panel | Class 1 |
| Smoke Density | Less then 450 flaming (ASTM E 662) |
| Static Test | Less then 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |

Colorways




SRD13 Sand



SRD14 Glacier



SRD45 Seascape



SRD46 Cadet



SRD53 Dockside




SRD54 Pepper



SRD56 Dorsal



SRD58 Cauldron



SRD59 Carbon



SRD73 Toast



SRD76 Truffle



SRD77 Pinecone