



When it comes to ultimate adaptability to numerous flooring types, **DYNAMIC®** holds the market. Breaking all the rules, this revolutionary product saves time with its instant access to light traffic. Dynamic® provides the waterproof benefits of a hard-set adhesive while aggressively retaining PSA-like surface tack.

**Shelf Life: 2 Years**



AVAILABLE IN 1- AND 4-GALLON PAILS


### PRODUCT BENEFITS

- Immediate access for light traffic (PSA)
- ColorReady® technology improves install accuracy
- High-strength, waterproof bond
- PSA performance with hard-set resilience
- LEED v4 contributing
  - VOC content 11 g/L (meets SCAQMD Rule 116B)
  - CDPH/EHLB Standard Method v1.2
  - Does not contain methylene chloride and perchloroethylene
  - Contributes to low emitting materials

### APPROVED FLOORING TYPES

- LVT/LVP
- Carpet tile (hard- and soft-backed)
- Sheet goods (vinyl, homogeneous, heterogeneous, fiberglass)
- Rubber (tile and sheet)
- WPC/WSC
- Cork-backed hard surface
- Cork underlayment
- VCT/VET
- Broadloom carpet (breathable and vinyl-backed)
- Carpet cushion to substrate
- Stair treads (rubber and vinyl)

### APPLICATION METHODS



90-350 sf/gal

Note: Coverage range dependent upon substrate composition and porosity, application method and flooring type.

### CERTIFICATIONS



RH



99%

pH



5-12

MVER



12 lbs

\*DRY TIME



30-60 min

\*WORKING TIME



12 hrs

CURE TIME



12 hrs

\*LIGHT TRAFFIC



0 min

HEAVY TRAFFIC



24 hrs

HEAVY ROLLING LOADS



48 hrs

\*Data icons reference PSA usage only. See technical data sheet for details.