







# INTUITIVE COLLECTION

The Intuitive Collection was designed with your entire commercial space in mind. These four complementary styles bring the perfect balance of fresh colors and visual texture that work seamlessly together throughout the interior.

### CONTEMPLATE

## PURE & SIMPLE

#### **RUMINATE**

#### **SMART & SHARP**

Style Number2865ProductTypeBroadloomConstructionTuftedSurface AppearanceGraphic Loop

Gauge 1/10" (39.37 rows per 10 cm)

Density 5,425

Dye Method100% Solution DyedFiber TypeColorstrand® SD NylonStain Release TechnologyMohawk Protection Plus StainSoil Release TechnologyMohawk Protection Plus SoilPrimary BackingWoven Polypropylene

Secondary Backing Weldlok®

Warranties

Indoor Air Quality Green Label Plus Certified # 8216

Size 12' width (3.66 m)

Flammability ASTM E648 Class 1 (Glue down)

Smoke Density ASTM 662 Less than 450

Static Propensity ATTCC-134 Under 3.5 KV

Lifetime Limited Wear
Lifetime Limited Static Protection
Lifetime Limited Colorfastness to Light
10 Year Limited Stain Resistance
10 Year Limited Colorfastness to
Atmospheric Contaminants

2B48 Broadloom Tufted Graphic Loop

1/10" (39.37 rows per 10 cm)

7,765

100% Solution Dyed Colorstrand® SD Nylon Mohawk Protection Plus Stain Mohawk Protection Plus Soil Woven Polypropylene

Weldlok®

Green Label Plus Certified # 8216

12' width (3.66 m)

ASTM E648 Class 1 (Glue down)
ASTM 662 Less than 450
ATTCC-134 Under 3.5 KV
Lifetime Limited Wear
Lifetime Limited Static Protection
Lifetime Limited Colorfastness to Light
10 Year Limited Stain Resistance
10 Year Limited Colorfastness to

Atmospheric Contaminants

2B64
Broadloom
Tufted
Graphic Loop

1/10" (39.37 rows per 10 cm)

5,824

100% Solution Dyed
Colorstrand® SD Nylon
Mohawk Protection Plus Stain
Mohawk Protection Plus Soil
Woven Polypropylene

Weldlok®

Green Label Plus Certified # 8216

12' width (3.66 m)

ASTM E648 Class 1 (Glue down) ASTM 662 Less than 450 ATTCC-134 Under 3.5 KV

Lifetime Limited Wear

Lifetime Limited Static Protection Lifetime Limited Colorfastness to Light 10 Year Limited Stain Resistance 10 Year Limited Colorfastness to Atmospheric Contaminants 2B49

Broadloom Tufted

Graphic Loop

1/10" (39.37 rows per 10 cm)

5,824

100% Solution Dyed
Colorstrand® SD Nylon

Mohawk Protection Plus Stain Mohawk Protection Plus Soil Woven Polypropylene

Weldlok®

Green Label Plus Certified # 8216

12' width (3.66 m)

ASTM E648 Class 1 (Glue down)

ASTM 662 Less than 450 ATTCC-134 Under 3.5 KV

Lifetime Limited Wear

Lifetime Limited Static Protection Lifetime Limited Colorfastness to Light 10 Year Limited Stain Resistance 10 Year Limited Colorfastness to Atmospheric Contaminants

Cover: Contemplate 521 with Town Center II 30 548 Graphite, Smart & Sharp 521 with Choice Step P010S Farmhouse Brown Ruminate 521, Pure & Simple 521 with Choice Step P006S Dovetail Gray



COLORSTRANDSD



Up to 2,000 sq. yds. available within 10 business days or less