

## **REPURPOSE AND REPLENISH**

Transform any commercial space with the small-scale patterns of Repurpose and Replenish. Both broadloom styles offer balance and versatility in traditional or modern design schemes.

**ProductType** Construction Surface Appearance Gauge **Tufted Weight PileThickness** Stitches Per Inch Density Weight Density Dye Method FiberType Stain Release Technology Soil Release Technology **Primary Backing** Secondary Backing NSF 140 Pattern Repeat Indoor Air Quality Size/Width Flammability Smoke Density Static Propensity Appearance Retention Rating (TARR) Warranties

## **REPURPOSE**

Broadloom Tufted Textured Patterned Loop 1/10" (39.37 rows per 10 cm) 22 oz/yd<sup>2</sup> (746 g/m<sup>2</sup>) .154" (3.91mm) 11.6 (45.67 per 10 cm) 5,143 113,146 76% Solution Dyed / 24% Yarn Dyed Colorstrand<sup>®</sup> Nylon Mohawk Protection Plus Stain Mohawk Protection Plus Soil Woven Polypropylene Weldlok® Gold 1.2" (W) × 1.5" (L) Green Label Plus Certified # 8216 12" width (3.66m) ASTM E 648 Class 1 (Glue down) ASTM 662 Less than 450 AATCC-134 Under 3.5 KV Severe Traffic Lifetime Limited Wear Warranty LIfetime Limited Static Protection Lifetime Limited Stain Resistance (Food & Beverage Only)

## **REPLENISH**

Broadloom Tufted Textured Patterned Loop 1/10" (39.37 rows per 10 cm) 22 oz/yd2 (746 g/m2) .141" (3.58 mm) 11.6 (45.67 per 10 cm) 5.617 123,574 78% Solution Dyed / 22% Yarn Dyed Colorstrand® Nylon Mohawk Protection Plus Stain Mohawk Protection Plus Soil Woven Polypropylene Weldlok® Gold 1.2'' (W)  $\times 0.8''$  (L) Green Label Plus Certified # 8216 12" width (3.66m) ASTM E 648 Class 1 (Glue Down) ASTM 662 Less than 450 AATCC-134 Under 3.5 KV Heavy Traffic Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Stain Resistance (Food & Beverage Only)

Cover: Repurpose 878 Redefined and Replenish 878 Redefined

## Repurpose

