

**M** | **Flex** PRODUCT SPECIFICATIONS




<b>COLLECTION</b>	Flex & Yield
<b>STYLE NUMBER</b>	10279
<b>PRODUCT TYPE</b>	Modular
<b>CONSTRUCTION</b>	Multi-Level Pattern Loop
<b>FIBER TYPE</b>	Eco Solution Q® Nylon
<b>DYE METHOD</b>	100% Solution Dyed
<b>PRIMARY BACKING</b>	Non-Woven Synthetic
<b>SECONDARY BACKING</b>	Ecoworx
<b>PROTECTIVE TREATMENTS</b>	SSP® Shaw Soil Protection

<b>PRODUCT SIZE</b>	24 inches x 24 inches	<b>Metric Units</b>	60.96 cm x 60.96 cm
<b>GAUGE</b>	1/10 inches		39.37 per 10 cm
<b>STITCHES</b>	12 per inches		45 per 10 cm
<b>FINISHED PILE THICKNESS</b>	0.125 inches		3.18 mm
<b>AVERAGE DENSITY</b>	5184 oz/yd <sup>3</sup>		10.16
<b>TOTAL THICKNESS</b>	0.264 inches		6.71 mm
<b>TUFTED YARN WEIGHT</b>	18 oz/yd <sup>2</sup>		610.3 g/m <sup>2</sup>
<b>GSA APPROVED PRODUCT</b>	Yes		

<b>US Units</b>	24 inches x 24 inches
	1/10 inches
	12 per inches
	0.125 inches
	5184 oz/yd <sup>3</sup>
	0.264 inches
	18 oz/yd <sup>2</sup>
	Yes

<b>Metric Units</b>	60.96 cm x 60.96 cm
	39.37 per 10 cm
	45 per 10 cm
	3.18 mm
	10.16
	6.71 mm
	610.3 g/m <sup>2</sup>

### Installation Methods



### Performance Testing

<b>PILL TEST</b>	Pass
<b>RADIANT PANEL</b>	Class I
<b>NBS SMOKE</b>	Less than 450
<b>ELECTROSTATIC PROPENSITY</b>	Less than 3.5 kv
<b>CRI GREENLABEL PLUS</b>	GLP9968
<b>ADA COMPLIANCE</b>	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

# M | Flex

## Environmental Specifications

**RECYCLABILITY** 100% Recyclable

## Materials

### Ingredients

**DOES NOT CONTAIN** does not contain PVC, phthalates or PBD/PBDE

### Recycled Content

**TOTAL RECYCLED CONTENT (BY WEIGHT)** 40.5%

**PRE-CONSUMER** 28%

**POST-CONSUMER** 12.5%

**BIO-BASED/RAPIDLY RENEWABLE CONTENT (BY WEIGHT)** 0%

**PACKAGING** 100% Recyclable

**COUNTRY OF ORIGIN (MANUFACTURER)** USA

Meets or exceeds all local and national regulations in country of manufacture. Manufactured in an ISO9001 & ISO14001 certified facility or equivalent. Recycled content is calculated using system allocation, mass balance, and direct insertion. The actual recycled content in this product will likely vary. For more information email [info@patcraft.com](mailto:info@patcraft.com).

## Third Party Certifications

<b>MBDC CRADLE TO CRADLE</b>	Silver Certified
<b>NSF 140</b>	Platinum Certified
<b>CRI GREEN LABEL PLUS</b>	Certified GLP9968
<b>USGBC LEED</b>	contributes
<b>BUILDING RESEARCH ESTABLISHMENT</b>	certified
<b>GOOD ENVIRONMENTAL CHOICE AUSTRALIA</b>	certified

Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice. This carpet is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another carpet design is also strictly prohibited. Visit [patcraft.com/testing](http://patcraft.com/testing) for more information.